



GREEN FINISH-X

HIGH-PERFORMANCE, **ENVIRONMENTALLY** FRIENDLY FLOOR COATING

PROPERTIES

Heavy-duty floor coating with environmentally friendly formula.
Low maintenance and easy removal of coating damage.
Deeper, longer-lasting high shine despite zinc-free formula; free from APEO and ammonia.
Resistant to abrasion, easily restorable and does not yellow.
Low emissions values; formula meets the new 1% VOC regulation.

SUITABILITY

Suitable for all absorbent and coatable floorings.

APPLICATION

Preparation of the floor: Thoroughly remove old sealers, waxes and coatings. For best results use a single-disc machine with a deep cleaning pad. Remove residues in edges and corners. Rinse thoroughly that no cleaner or liquor residue left on the floor.

Application of the coating: The floor must be completely dry before the coating is applied. Apply the coating in thin, even layers with a clean professional flat mop or Floor-Finish coating mop. Under normal conditions, 20-30 minutes are sufficient drying time between individual coats. For optimal results, apply at least 2 coats, but no more than 4 coats of GREEN FINISH-X within 24 hours.

Daily care: 1. Remove dust from the floor daily or as needed with a synthetic acrylic mop.
2. Wipe daily with GLOSS SYSTEM1 pH-neutral floor cleaner.

Shine renewal: Use CITRUS 2in1 1:64 with water (16 ml per liter water) with a mop or scrubbing machine to remove abrasion and heel marks. Allow the floor to dry and polish with an ultra-high-speed machine with appropriate pad. Due to the use of CITRUS 2IN1 in conjunction with an ultra-high-speed machine, the floor gets maximum shine and eliminates frequent cleaning and post-coating.

Recoating: When it is no longer possible achieve a high gloss with Citrus 2in1, you should use SURF diluted 1:16 for deep cleaning. Prepare the surface to be coated with a red or blue pad, suck up the liquid, mop the floor with a suitable mop, allow to dry, and then apply 1-2 coats of GREEN FINISH-X.



UL classified as slip-resistant



pH value in concentrate

7,5



Containers

ART.-NO.

5 L

GF-X05

- **Type:** Zink-free acrylic mix
- **Form:** Impermeable liquid
- **Fragrance:** Mild
- **Color:** White
- **Drying time:** 30 minutes
- **Solids:** 20%
- **Slip resistance:** UL classified slip resistant
- **Yield:** ca. 60m² / liter

- Before use, always read the indications and product information
- For commercial / industrial use only!
- Reusable containers



Achtung

Contains 2-(2-ethoxyethoxy) ethanol,
Tris (2-butoxyethyl) phosphat
Causes serious eye irritation

- Read the identification label before using. Keep out of the reach of children. If medical advice is needed, have product container or label at hand.
- Wear eye or face protection. Wash your hands thoroughly after use.
- If contacted with the eyes wash with a large quantity of water for several minutes. Remove contact lenses, if present and continue the rinsing.

