Compilation date: 17.10.2017 Revision date: 15.12.2017

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

FOAMEX-DRY

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Inapplicable.

1.3 Details of the supplier of the safety data sheet

Company name: Arcora International GmbH

Street: Marsstraße 9

Place: 85609 Aschheim by Munich

Germany

Tel: +49 (0)89 / 14 33 29 3-0 Fax: +49 (0)89 / 14 33 29 3-29

E-Mail: info@arcora.de

1.4 Emergency telephone number + 49 (0) 89 / 14 33 29 3-10

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Hazard categories:

Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Aquatic Chronic 3, H412

Hazard Statements:
Harmful if swallowed or in contact with skin.

Causes serious eye irritation.

Causes skin irritation.

Harmful to aquatic life with long lasting effects.

2.2 Label elements

Signal word: Warning Pictograms: GHS07



Hazard statements

H302+H312+H332 Harmful if swallowed or in contact with skin.

according to Regulation (EC) No 1907/2006

FOAMEX-DRY

Compilation date: 17.10.2017 Revision date: 15.12.2017

Page 2 of 16

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

General: Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Prevention: Wear protective gloves. Wear eye or face protection. Wear protective clothing.

Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or physician if you feel unwell.

Storage: Not applicable

Disposal: Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazardous ingredients:

2-butoxyethanol

Supplemental label elements

Contains (R)-p-mentha-1,8-diene, citral and reaction mass of: 5-chloro-2-methyl4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.1 Mixtures

Hazardous components

EG-No.	Chemical name	Quantity
CAS-No.		
Directory	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH-No.		
271-557-7	Sulfuric acid, MonoC10-16-alkyl esters, sodium salts	≥ 16 - < 25
68585-47-7		
	Acute Tox. H302	
203-905-0	2-Butoxyethanol	≥ 11 - < 18
111-76-2		
603-014-00-0	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
200-661-7	2-Propanol	≥ 2 - < 3
67-63-0		
603-117-00-0	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
227-813-5	(R)-p-Mentha-1,8-dien	≥ 0.3 - < 1
5989-27-5		




according to Regulation (EC) No 1907/2006

FOAMEX-DRY

Compilation date: Revision date: 17.10.2017 15.12.2017

Page 3 of 16



Full text of H and EUH statements: see section 16.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.



according to Regulation (EC) No 1907/2006

FOAMEX-DRY

Compilation date: Revision date:

17.10.2017 15.12.2017





No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

Harmful if inhaled.

Harmful in contact with skin. Causes skin irritation.

Harmful if swallowed.

Over-exposure signs/symptoms:

Inhalation No specific data.

Skin contact Adverse symptoms may include the following: irritation redness

Eye contact Adverse symptoms may include the following:

pain or irritation watering redness

Ingestion No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products:

Decomposition products may include the following materials: carbon dioxide carbon monoxide.

5.3 Advice for firefighters

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.



according to Regulation (EC) No 1907/2006

FOAMEX-DRY

Compilation date: Revision date:

17.10.2017 15.12.2017

Page 5 of 16

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.



Compilation date: Revision date:

17.10.2017 15.12.2017

Page 6 of 16



7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits (TRGS 900)

Product/ingredient name	Exposure limit values
	Arbejdstilsynet (Denmark, 10/2012). Absorbed through skin.
2-butoxyethanol	TWA: 20 ppm 8 hours.
	TWA: 98 mg/m³ 8 hours.
	Arbejdstilsynet (Denmark, 10/2012).
2-propanol	TWA: 200 ppm 8 hours.
	TWA: 490 mg/m³ 8 hours.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following:



according to Regulation (EC) No 1907/2006

FOAMEX-DRY

Compilation date: Revision date:

17.10.2017 <u>15.12.2</u>017

Page 7 of 16



European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

according to Regulation (EC) No 1907/2006

FOAMEX-DRY

Compilation date: Revision date:

17.10.2017 15.12.2017

Page 8 of 16

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: liquid colourless

Odour: citrus

Test method

Ph-value (at 20 °C): 6-7

Changes in the physical state

Melting point: approx. 0 °C
Initial boiling point and boiling range: approx. 100 °C

Flash point: Closed cup: 62.77°C

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Auto-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined

Oxidizing properties

not oxidising.

Vapor pressure: < 4 kPa (bei Raumtemperatur)

Density: 1,01 g/cm³
Water solubility: not available

Compilation date: 17.10.2017 Revision date: 15.12.2017

Page 9 of 16

Solubility in other solvents

not determined

Partition coefficient: not applicable Dyn. Viscosity (at 25 °C): not applicable

Vapour densitiy: < 1

Evaporation rate: not determined

VOC-content: VOC is applicable to use dilution product.

9.2 Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

No specific data.

10.5 Incompatible materials

No specific data.

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

CAS-No.	Chemical name				
	Exposure way	Method	Dose	Species	Source
	Sulfuric acid, MonoC10-16-alk	ylester, sodium salt	s		
	oral	LD50	2000 mg/kg	Rat	
	2-butoxyethanol	<u> </u>			
	oral	LD50	250 mg/kg	Rat	
	dermal	LD50	220 mg/kg	Rabbit	
	inhalative gas (4 h)	LC50	450 ppm	Rat	



Compilation date: Revision date:

17.10.2017 15.12.2017

Page 10 of 16



2-Propanol			
oral	LD50	5000 mg/kg	Rat
dermal	LD50	12800 mg/kg	Rabbit
(R)-p-Mentha-1,8-dien			
oral	LD50	4400 mg/kg	Rat
dermal	LD50	> 5000 mg/kg	Rabbit
oral	LD50	3.45 g/kg	Rat
dermal	LD50	2250 mg/kg	Rabbit

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Obsevation
2-Butoxyethanol	Eyes - Moderate irritan	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
2-Propanol	Eyes - Moderate irritan	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
(R)-p-Mentha-1,8-dien	Skin - Mild irritant	Rabbit	-	24 hours 10 %	-
Citral	Skin - Moderate irritant	Guinea pig	-	48 hours 1 %	-
	Skin - Severe irritant	Guinea pig	-	24 hours 100 mg	-
	Skin - Mild irritant	Human	-	24 hours 40 mg	-
	Skin - Severe irritant	Man	-	48 hours 16 mg	-
	Skin - Severe irritant	Pig	-	48 hours 50 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 100 mg	-

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-Propanol	Category 3	Not applicable	Narcotic effects

Compilation date: Revision date:

17.10.2017 15.12.2017

Page 11 of 16

Possible acute effects on health

Causes serious eye irritation.

Harmful if inhaled.

Harmful in contact with skin. Causes skin irritation.

Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristic

Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

pain or irritation redness

Eye contact Adverse symptoms may include the following:

pain watering redness

Ingestion No specific data.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Sulfuric acid, monoC10-16- alkyl esters, sodium salts	Acute EC50 1.37 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute EC50 >1000 mg/l Fresh water	Daphnie - Daphnia magna	48 hours
2-butoxyethanol	Acute LC50 800000 μg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours
2-propanol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
2 propartor	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
	Acute EC50 421 μg/l Fresh water	Daphnie - Daphnia magna	48 hours
(R)-p-mentha-1,8-dien	Acute EC50 688 μg/l Fresh water	Fish - Pimephales promelas Juvenile (Fledgling, Hatchling, Weanling)	96 hours

12.2 Persistence and degradability

Not available

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Sulfuric acid, MonoC10-16-alkylester, sodium salts	-	-	readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol	0,8	-	Low
2-Propanol	0,051	-	Low



Compilation date: Revision date:

17.10.2017 15.12.2017

Page 12 of 16

(R)-p-Mentha-1,8-dien	4,38	1022	High
Citral	2,76	89,72	Low

12.4 Mobility in soil

Not available

12.5 Results of PBT and vPvB assessment

Not available

12.6 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

The classification of the product may meet the criteria for a hazardous waste.

Packaging

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN-number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

14.3 The transport hazard class

14.4 Packing group

Other relevant information about land transport

lapse

Compilation date: Revision date:

17.10.2017 15.12.2017

Page 13 of 16

Inland waterways transport (ADN)

14.1 UN-number

No dangerous good in sense of these transport regulations.

- 14.2 UN proper shipping name
- 14.3 The transport hazard class
- 14.4 Packing group

Other relevant information about Inland waterways transport

lapse

Marine transport (IMDG)

14.1 UN-number

No dangerous good in sense of these transport regulations.

- 14.2 UN proper shipping name
- 14.3 The transport hazard class
- 14.4 Packing group

Other relevant information about marine transport

lapse

Air transport (ICAO)

14.1 UN-number

No dangerous good in sense of these transport regulations.

- 14.2 UN proper shipping name
- 14.3 The transport hazard class
- 14.4 Packing group

Other relevant information about air transport

lapse

14.5 Environmental hazards

no

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information (EG) No. 1907/2006 (REACH)

Annex XIV the list of substances subject to authorisation.



according to Regulation (EC) No 1907/2006

FOAMEX-DRY

Compilation date: Revision date:

17.10.2017 15.12.2017

Page 14 of 16

Annex XIV

None of the components are listed.

Substances of Very High Concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable

Other EU-Community regulations

All components are listed or exempted.

Seveso Directive

This product is controlled under the Seveso Directive.

National regulations

Danish fire class: II-1 MAL-code: 3-3

Protection based on MAL: According to the regulations on work involving coded products, the

following stipulations apply to the use of personal protective

equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 3-3 Application:

When spraying in new* booths if the operator is outside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Air-supplied half mask and eye protection must be worn.

During downtimes, cleaning and repair of closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone.

- Air-supplied half mask, coveralls and eye protection must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.



according to Regulation (EC) No 1907/2006

Compilation date: Revision date:

17.10.2017 15.12.2017

FOAMEX-DRY



Page 15 of 16

- Air-supplied full mask, arm protectors and apron must be worn.

During non-atomizing spraying in existing* facilities of the combinedcabin, spraycabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask, arm protectors and apron must be worn.

During all spraying where atomization occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution:

The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use:

Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order on young people's dangerous work.

15.2 Chemical Safety Assessment

This product contains a substance(s) for which a chemical safety assessment is not required because it is below the maximum allowable import threshold under REACH.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Process categories according to ECHA guidance on information requirements and chemical safety assessment, chapter R.12:

according to Regulation (EC) No 1907/2006

FOAMEX-DRY

Compilation date: Revision date:

17.10.2017 15.12.2017

Page 16 of 16



PROC 1: Use in closed processes.

PROC 8 Dilution of concentrated products, application of drain cleaners, dosage of textile washing agents.

PROC 10 (Roller application or brushing): Processing without large-scale spraying.

PROC 11 ((Spraying outside industrial settings): Processing with large-scale spraying (e. g. high pressure cleaning, foam gun).

PROC 19 (Hand-mixing with intimate contact): Hand cleaning and disinfection.

Relevant H and EUH statements (number and full text)

11005	
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness and dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.