# **FLOOR COATING**



**HIGH-GLOSS** 



# DISINFECTANT AND ALCOHOL RESISTANT FLOOR COATING



This high-quality, disinfectant and alcohol resistant floor coating is manufactured from plastic dispersions and used to protect flooring in areas where surface and hand disinfectants are in frequent use. ELITE 29 produces a long-lasting, restorable result and is easy to recoat without the need of an additional deep cleaning.

#### SUITABILITY

ELITE 29 is used on PVC, polyolefin, linoleum, absorbent natural and artificial stone, asphalt, etc. This high-quality floor coating is used in hospitals, nursing homes, kindergartens and sanatoriums. For flooring with a PU or PE top layer, an adhesion test should be carried out before proceeding.

## APPLICATION

**Preparation of the floor:** Thoroughly remove old sealers, waxes and coatings. For best results use a single-disc machine with a deep cleaning pad. Remove residues in edges and corners. Rinse thoroughly that no cleaner or liquor residue left on the floor.

**Application of the coating:** The floor must be completely dry before the finish is applied. Apply the coating in thin, even layers with a clean professional flat mop or Floor-Finish coating mop. Under normal conditions, 30 minutes are sufficient drying time between coats. For optimal results, apply at least 2 coats, but no more than 3 coats of ELITE 29 within 24 hours.

Daily care: Mop the floor on a daily basis with GLOSS SYSTEM1 or FLEXON.

**Shine renewal:** Use CITRUS 2IN1 in a mixing ratio of 1:64 with cold water (16 ml/1 ltr water). Apply the liquid with a mop or a scrubbing machine to remove heel marks or scratches. Allow the floor to dry and polish it with a UHS-polishing machine and the right pad.

**Recoating:** If you can not generate the high gloss wit CITRUS 2IN1 anymore you have to use SURF 1:16 mixed with cold water for the deep cleaning.

Work on the coating surface with a red or blue pad, soak the liquid, mop the floor and let it dry. Afterwards you can apply 1-2 new coating layers of ELITE 29 for a refreshed and glossy finish.

### INGREDIENTS

< 5% nonionic surfactants, < 5% phosphate, acrylates, polymers, wax, Methylchloroisothiazolinone, Methylisothiazolinone.

Before use, always reactive indications and product information.
For commercial / industrial use only!
Beusable containers

Product usage: ca. 25 ml/m<sup>2</sup> per layer

Attention: Bottom temperature not below 10 ° C <u>Protect from frost!</u>



Marsstraße 9 • 85609 Aschheim near Munich - Germany Fon: +49 (0)89 -14 33 29 30 • Fax: +49 (0)89 - 14 33 29 329

www.arcora-group.com info@arcora.de



ARCORA



pH value in concentrate 8,5

4

Containers

 $\cap$ 

8 10 12 14

ART.-NO.

01152-05

