




SATIN-EFFECT

MFMA
approved



UL classified slip resistant



pH-value in concentrate

7,5–8,5

0 2 4 6 8 10 12 14

Containers

ART.-NO.

5 L

01081-05

- Before always read the indications and product information.
- For commercial / industrial use only!!
- Reusable containers

- **Type:** Urethane/acrylic blend
- **Form:** Impermeable liquid
- **Fragrance:** Mild
- **Color:** White/Beige
- **Drying time:** 60 minutes
- **60° gloss:** < 30
- **Solids:** 29 %
- **Slip resistance:** UL classified slip resistant
- **Yield:** ca. 20 m²/liter

Harmful to aquatic life with long lasting effects.

- Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Avoid release to the environment.
- Dispose of contents and container in accordance with all local, regional, national and international regulations.

WOOD SATIN FINISH

WATER-BASED URETHAN WOOD COATING WITH SATIN-EFFEKT

PROPERTIES

This water-based, urethane/acrylic wood floor finish provides long lasting beauty and protection for all wood floors. Specially manufactured for coating sealed and oiled solid wood floors.

- No added catalyst required
- High solids content of 29%
- Dries very quickly - in 60 min.
- Creates a high-gloss transparent film
- Very durable
- Very high abrasion resistance
- Dirt resistant
- UL classified as slip resistant

Apply the one-component system with a clean professional flat mop (Wischwiesel) or Floor-Finish coating mop.

Note: WOOD SATIN FINISH is **not suitable for use on untreated wooden floors**. Use it only on wooden floors that haben been sealed with WOOD PRIMER.

APPLICATION

Preparing the ground:

For an optimal result, you should apply 1-2 coats WOOD SATIN FINISH over WOOD PRIMER within 4 hours. Before applying WOOD SATIN FINISH, the WOOD PRIMER must be completely dried out. Ensure adequate ventilation during all phases of the coating process.

Application of WOOD SATIN FINISH:

Shake well before opening. Apply approx. 1 Liter per approx. 20 m². The WOOD SATIN FINISH can be applied with a clean professional flat mop or Floor-Finish coating mop. Apply the layers at an even pace and overlapping in the grain direction of the wood. Allow the individual layers to dry for at least 1 hour before applying another layer. In moist ambient conditions, a longer drying time is required. Apply a second layer after drying the first layer. Grinding of the first layer is only necessary if a swelling of fibers has occurred or if the layer has dried for more than 4 hours. In this case, sand the floor with a previously used 120 grip pad or ABRASIV HI-PRO pad. After grinding, always thoroughly vacuum and wipe. Depending on the surface finish, 1-2 layers of approx. 60 min. necessary.

Daily care:

1. Remove dust from the floor daily or as needed with a synthetic acrylic mop.
2. Wipe daily with GLOSS SYSTEM1 pH-neutral floor cleaner.

Shine renewal:

Use CITRUS 2in1 1:64 with water (16 ml per liter water) with a mop or scrubbing machine to remove abrasion and heel marks. Allow the floor to dry and polish with an ultra-high-speed machine with appropriate pad.

Recoating:

Method 1: When it is no longer possible achieve a high gloss with CITRUS 2IN1, you should use SURF diluted 1:16 for deep cleaning. Prepare the surface to be coated with a red or blue pad, suck up the liquid, mop the floor with a suitable mop, allow to dry, and then apply 1-2 coats of WOOD SATIN FINISH.

Method 2 (Intensive): Clean the floor with synthetic acrylic mop, if there are chewing gums and adhesive labels, remove completely. Clean the soil with a 1:16 dilution with SURF. To sufficiently level the ground, grind with a 120 grip pad or ABRASIV HI-PRO pad. Wipe the floor with a suitable mop cover until all residues are removed and then apply 1-2 layers of WOOD SATIN FINISH.

Note: Test floors that have been coated beforehand in an inconspicuous place before applying a new layer to determine whether the new application is compatible with the old finish. Apply 1-2 layers WOOD SATIN FINISH. Observe the above instructions for applying finish.

We accept no liability for damage caused by improper use.

