

SPRAY EXTRACTION MACHINE

aniko®60

SPRAY EXTRACTION MACHINE



PROPERTIES

ANIKO60 is a spray extraction machine for the professional cleaning of medium-sized carpet surfaces.

Despite its powerful and compact design, it is easy to carry and suitable for professional use in building cleaning. Thanks to the high suction power of the ANIKO60, as much dirt as possible is extracted from the floor and very fast drying is possible. Its small working width of only 30 cm allows cleaning in confined spaces.

Further properties

- incl. suction lance for carpets
- robust construction, tank made of polyethylene with high tightness
- easy handling
- Ideal for professional cleaning work in the building cleaning industry
- Coupling made of brass, suction motor with thermal protection against overloading
- Height-adjustable handle for better ergonomics
- Diaphragm pump with By-Pass

APPLICATION AREA

Suitable for use in cleaning companies, hotels, restaurants, pubs, bars, offices, banks, carpet shops, trains, buses, airplanes, cinemas, theatres, ships as well as in public facilities.



DETAILS

Article no.:
units:

ANIKO60
1 SET

SPECIAL ACCESSORIES



Upholstery adapter off Plastic for cleaning of upholstery and heavy accessible corners

Article no.:

01253

SONDERZUBEHÖR



Upholstery adapter off Aluminium for cleaning of upholstery and heavy accessible corners

Article no.:

01252

TECHNISCHE DATEN

| | |
|---------------------------------|--------------------------|
| Dimensions | 38x50x78 cm |
| Packing dimensions | 42x65x91 cm |
| Machine weight | 24 kg |
| Weight including packaging | 33 kg |
| Suction motor / max. air output | zweistufig / 45 l/sec |
| Max. Power | 1500 W |
| Water column | 3000 mmH ₂ O |
| Power Pump with By-Pass | 80 W, 9,0 bar, 4,5 l/min |
| Fresh water tank | 30 Liter |
| Dirty water tank | 30 Liter |
| Number of nozzles | 3 |
| Cable length | 10 m |
| Length of hose | 5 m |
| Area output | 80 m²/h |
| Volume | 67 db |

