

HEAVY-DUTY FLOOR CLEANERS

PREMIUM QUALITY

MADE IN GERMANY



EXBETAN-X

WORKSHOP AND INDUSTRIAL CLEANER

PROPERTIES

Highly concentrated special cleaner for heavy soiling in the workshop Workshop, motor vehicle and commercial vehicle areas. Cleans quickly, effortlessly and gently. Effortlessly and thoroughly removes grease, oil, soot and and oil contamination, soot and stubborn dirt incrustations.

Oil separator-friendly according to Ö-NORM B 5105.

The product is EDTA-free and can therefore be fed into the sewage system without hesitation.

APPLICATION AREAS

For manual or machine cleaning of alkali- and water-resistant materials of all kinds, such as hard flooring made of synthetics and natural stone and industrial flooring. Universally applicable as high-pressure cleaner, spray cleaner, ultrasonic cleaner, fuel pump cleaner, and engine cleaner. Check material compatibility before applying. We do not assume liability for damages caused by improper use.

APPLICATION / DOSING

Manual cleaning:

Dilute 100–500 ml to 10 liters of water

Floor cleaning:

Dilute 50–100 ml to 10 liters of water

Automatic use:

Dilute 200–500 ml to 10 liters of water

High-pressure cleaning:

Dilute in the suction tank: 1000 ml to 10 liters of water

Spray cleaning:

In the sprayer, dilute between 1:1 and 1:5 with water

INGRIDIENTS

< 5 % non-ionic surfactants, < 5 % phosphonate, perfume

- Condition: Liquid
- Color: light yellow
- Odor: CHARACTERISTIC

Caution!

Causes severe eye irritation.

- Do not breathe dust/fume/gas/mist/vapour/aerosol.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF INHALED: Remove the person to fresh air and ensure unobstructed breathing.
- Immediately call POISON CENTER RUM/doctor.

Follow the instructions for use on the observe the label. The information based on the current state of our knowledge, however, they do not represent guarantee of product characteristics and do not establish a contractual legal relationship. Safety data sheet available on request.



pH-value (at 20°C)

11,3

0 2 4 6 8 10 12 14

CONTAINERS

ART.-NO.

10 L

01025



ARCORA® INTERNATIONAL

Marsstraße 9 • 85609 Aschheim near Munich - Germany
Fon: +49 (0)89 - 14 33 29 30 • Fax: +49 (0)89 - 14 33 29 329

www.arcora-group.com
info@arcora.de