


THE INEXPENSIVE ALL-ROUNDER AMONG MOP COVERS!



Special Cover sheet 100% PES



Bag material made of 100% PES with inserts Tear resistant & water permeable





SPECIFICATIONS

Yarn mixture:

Yarn colour:

Cover sheet:

Bag material:

Shrinkage value:

4-colour coding:

Washing label:

100% PES/MF BLUE -WHITE 100% woven polyester 100% woven polyester 2-3% Embroidery label in WHITE, embroidered on 2 sides BLUE, GREEN, YELLOW, RED

MADE IN EEC

Size:	40 cm	50 cm
Weight:	ca. 90 g	ca. 130 g
Units:	75 Stück	50 Stück
Article-no.:	MBW40DBFC	MBW50DBFC

SPECIAL FEATURES

The **EXCELLENT BLUE-WHITE DB-FC** impresses thanks to the tightly woven microfiber yarn with **improved mechanics** on the floor and **optimum cross-linking** of the cleaning solution. The high-quality woven microfiber enables **excellent dirt and water absorption** as well as a higher area performance thanks to the composition of the yarn. The smooth-running yarn, which does not scratch the floor, ensures **ergonomic and fatigue-free cleaning** and working. The cover sheet and pockets are made from 100% woven polyester material. The sponge insert in the pockets helps the holder to glide.

PROPERTIES

- Very good price-performance ratio
- Improved mechanics on the floor
- Optimum cross-linking of the cleaning solution
- Suitable for preparation
- High dirt and water absorption
- Long service life due to high-quality manufacturing process

APPLICATION

Can be used both dry and wet on smooth, laminated and unlaminated floor coverings.

APPLICATION AREA

For maintenance cleaning, as well as wet and dry cleaning of any surfaces, such as elastic coverings, hard coverings, porcelain stoneware, stone floors, tiles, laminate floors and ideally suited for smooth and porous floor coverings. Optimal for use in health care, clinics, retirement and nursing homes as well as public facilities and building cleaning.

WASHING RECOMMENDATION

It is advisable to wash the mop cover before use. A washing temperature of 60 °C is recommended. A maximum washing temperature of 95 °C should not be exceeded. The use of fabric softeners and bleaching agents should be avoided. Do not exceed 80 °C when drying.

ARCORA® INTERNATIONAL

Marsstraße 9 • 85609 Aschheim near Munich - Germany Tel.: +49 (0)89 -14 33 29 30 • Fax: +49 (0)89 - 14 33 29 329 www.arcora-group.com info@arcora.de